

38 Series Premium-line Guestroom Phone



38 Series Features:

- **Programmable Guest Service Keys** - Permanent one-touch memory keys
- **Easy Message Retrieval™** - Message Waiting Light, button and Ringer Indicator
- **Dual-Dial Keypads™** - Dialling keypad also on the handset for ultimate guest convenience
- **Speakerphone** (TSD models only) and Hold button with indicators
- **FacePlate Plus™** - full length faceplate and placard faceplate
- **Privacy Guard Redial™** - Last number dialled disappears after a defined time
- **SmartTray™** - stores the handset cord tidily and makes for easier cleaning
- **Auto-Connect™** - Resets the phone to receive incoming calls even when dislodged from the cradle
- **Express Programming** - Supports Remote Programming via Bittell's Express Programming devices

Product Datasheet



- Two line auto-select and three-way conference (Two Line phones only)
- Flexible Data Port
- Redial, Flash, Pause, Mute buttons (Flash and Pause time programmable)
- Ringer Volume HI/LOW adjustable
- Speakerphone and Handset volume three level adjustable, and stores the adjustment
- Handset with HAC
- Desk and Wall Mountable



Available Models:

| | | |
|-------------|---|----------------|
| HA38TS | Single Line Phone (no speaker) for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard | |
| | • No Guest Service Keys | HA38TS-P |
| | • 5 Guest Service Keys | HA38TS-5 |
| | • 10 Guest Service Keys | HA38TS-10 |
| HA38TSD | Single Line Speakerphone for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard | |
| | • No Guest Service Keys | HA38TSD-PS |
| | • 5 Guest Service Keys | HA38TSD-5S |
| | • 10 Guest Service Keys | HA38TSD-10S |
| HA38TSD-T | Two Line Speakerphone for the Guestroom with Flash, Redial, Hold, Cord Tray and Placard | |
| | • No Guest Service Keys | HA38TSD-TP |
| | • 5 Guest Service Keys | HA38TSD-T5 |
| | • 10 Guest Service Keys | HA38TSD-T10 |
| HA38C+TSD | Single Line Speakerphone for the Guestroom with additional Handset keypad, Flash, Redial, Hold, Mute, Conference Calling, Cord Tray, and Placard | |
| | • No Guest Service Keys | HA38C+TSD-PS |
| | • 5 Guest Service Keys | HA38 C+TSD-5S |
| | • 10 Guest Service Keys | HA38 C+TSD-10S |
| HA38C+TSD-K | Single Line Speakerphone for the Guestroom with LCD Clock and additional Handset keypad, Flash, Redial, Hold, Mute, Conference Calling, Cord Tray, and Placard | |
| | • No Guest Service Keys | HA38C+TSD-PSK |
| | • 5 Guest Service Keys | HA38C+TSD-5SK |
| | • 10 Guest Service Keys | HA38C+TSD-10SK |
| HA38C+TSD-T | Two Line Speakerphone for the Guestroom with additional Handset keypad, Flash, Redial, Hold, Mute, Conference Calling, Cord Tray, and Placard | |
| | • No Guest Service Keys | HA38C+TSD-TP |
| | • 5 Guest Service Keys | HA38C+TSD-T5 |
| | • 10 Guest Service Keys | HA38C+TSD-T10 |

Lobby Phones

| | |
|-----------|--|
| HA38TS-N | Single Line Lobby Phone, One Guest Service Key, and No Dial Pad |
| HA38TS-NK | Single Line Lobby Phone with LCD Clock, One Guest Service Key, and No Dial Pad |

Product Datasheet



Specifications:

| | |
|-----------------------------------|---|
| Phone Dimensions: | 22.5cm×16.5cm |
| Handset cord: | 3.66m (Length) |
| Line cord: | 2.0m(Length) |
| Weight: | 910g |
| Color: | Ivory / Black |
| Handset: | Hearing Aid Compatible (HAC) Handset |
| Dial Character: | Standard 12 group (DTMF) |
| Flash time: | 80ms, 100ms, 300ms, 600ms optional, standard is 600ms |
| Message Waiting Light Voltage: | Standard 90~150V DC Customized various MWL card compatible with PBX |
| Operating Voltage: | 24 ~ 60V DC |
| Quality Control: | ISO9001, ISO14001 |
| Quality Approval: | CCC, FCC, CE, RoHS (FCC Part 15 & 68 compliant) |
| One-Touch Memory Key Programming: | Manually Store(Yes) Hand-held Cloner R.P.(Yes) Master Cloner on line(Yes) |
| Box Dimensions: | 48×36×25.5(cm) |
| Package (set/carton): | 10set/Carton |



38 Series Speakerphone with Dual-Dial Keypad
(HA38C+TSD-5S)



38 Series Lobby Phone
(HA38TS-N)

Bittel Electronics (EU) Limited

50 Broadway
London SW1H 0RG
United Kingdom

Tel: +44(0)203 405 1200
Fax: +44(0)208 964 5886
Email: europe@bittelcom.com

www.bittelcom.eu